


DM-200P connector

0.6mm pitch

[Type]
For S.O.DIMM

[Current rating]
0.3A

[Voltage rating]
25V



Socket for DDR/DDR2 S.O.DIMM 200-circuits complying with JEDEC MO-224 standard.

DM-144P connector JEDEC-MO-190

0.8mm pitch

[Type]
For S.O.DIMM

[Current rating]
0.5A

[Voltage rating]
250V



This is sockets for the S.O.DIMM of 144-circuits based on the JEDEC MO-190 standard, and its side type socket is low profile with 5.2 mm height.


DM-144P connector JEDEC-MO-274

0.8mm pitch

[Type]
For S.O.DIMM

[Current rating]
0.5A

[Voltage rating]
250V



Socket for DDR2 S.O.DIMM 144-circuits complying with JEDEC MO-274 standard.


DM-72P connector

1.27mm pitch

[Type]
For DIMM

[Current rating]
0.5A

[Voltage rating]
250V



Standardized by JEDEC (MO-160). Straight type DIMM socket that is suited for module PC board with operating voltage 3.3V.*Module is easily ejected with the ejector button.*With 14mm height, wide variety of mounting is possible.


RSXA connector

2.5mm pitch

[Type]
IDC style

[Current rating]
4.0A (AWG#22)
2.0A (AWG#24)

[Voltage rating]
250V



This connector is 2.5 mm pitch card-edge type insulation displacement connector. •EConform with RAST 2.5 standard •EIDC (Insulation displacement connection) with twin U-slot contact design to provide extra stability. •EVarious polarizing features, keying option and locking features available. •EDaisy chain option available. •E2 to 10 Circuits *For Circuits 11 to 20, please contact us for availability and lead time.